

**STANDARD FEATURES**

- ◆ ¾ hp motors
- ◆ Galvanized steel fan wheels & housings
- ◆ Aluminum airfoil shaped directional vanes
- ◆ Aluminum base frame
- ◆ White aluminum or stainless steel housing
- ◆ Keyhole slots in backplate for quick wall mounting
- ◆ Licensed to bear AMCA Air Performance Seal
- ◆ UL Listed (United States & Canada)
- ◆ Five year parts warranty
- ◆ Crafted with Pride in the USA

MODEL WHITE ALUMINUM	MODEL STAINLESS STEEL	Nozzle Width (in)	Max. Velocity (fpm)	Avg. Outlet Velocity (fpm)†	Air Volume‡ (scfm)	# Motor(s) @ hp	Power Rating (kW)	Outlet Velocity Unif. (%)	# Fans	Net Wgt. (lbs)	Ship Wgt. (lbs)
<b>CUSTOMER ENTRY MODELS</b>											
ASF1036A	ASF1036A-SS	36"	2700	1337	958	1 @ ¾	.51	81.4	2	50	69
ASF1042A	ASF1042A-SS	42"	2700	958	978	1 @ ¾	.33	78.9	2	52	78
ASF1048A	ASF1048A-SS	48"	2700	1011	966	1 @ ¾	.53	59.4	2	53	80
ASF1060A-2*	ASF1060A-SS-2*	60"	2700	692	977	1 @ ¾	.31	26.0	2	54	110
ASF1060A-3**	ASF1060A-SS-3**	60"	2700	1006	1498	1 @ ¾	.40	70.0	3	60	116
ASF1072A	ASF1072A-SS	72"	2700	838	1467	1 @ ¾	.40	62.0	3	70	126
ASF2072A	ASF2072A-SS	72"	2700	1337	1916	2 @ ¾	1.02	81.4	4	80	136
<b>SERVICE ENTRY MODELS</b>											
ASR1036A	ASR1036A-SS	36"	3500	1965	1812	1 @ ¾	.68	71.9	2	50	69
ASR1042A	ASR1042A-SS	42"	3500	1716	1752	1 @ ¾	.75	78.6	2	52	78
ASR1048A	ASR1048A-SS	48"	3500	1504	1882	1 @ ¾	.73	54.6	2	53	80
ASR1060A*	ASR1060A-SS*	60"	3500	1225	1817	1 @ ¾	.74	27.0	2	54	90
ASR2060A**	ASR2060A-SS**	60"	3500	1805	2726	2 @ ¾	1.18	74.0	3	70	116
ASR2072A	ASR2072A-SS	72"	3500	1965	3624	2 @ ¾	1.36	71.9	4	84	130

\* Two blower system \*\* Three blower system  
For door widths in excess of 72" combine units.

<b>MOTOR VOLTAGES/AMP DRAWS</b>			
Horsepower	¾	¾	¾
Speed	1	1	1
Volts	120	208/240	480
Phase	1	1	1
Hertz**	50/60	50/60	50/60
Amps per Motor	7.5	3.8	1.8

\*\*Operation at 50 Hz will generate approximately a 17% reduction in performance.

Sound level measured 10' (3m) from the unit in free field:

<b>ASF (2 FAN)</b>	<b>58 dBA</b>
<b>ASF (3 FAN)</b>	<b>60 dBA</b>
<b>ASR (2 FAN)</b>	<b>67 dBA</b>
<b>ASR (3 FAN)</b>	<b>69 dBA</b>

AMCA Seal applies to air performance only.



<b>VELOCITY PROJECTION</b>			
<b>Model: ASF1036</b>			
Distance from Nozzle (ft)	2	3	5
Core Velocity (fpm)	1555	1011	900
<b>Model: ASR1036</b>			
Distance from Nozzle (ft)	3	5	7
Core Velocity (fpm)	2060	1555	1300



Berner International Corporation certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.

Rated data shown is for base unheated units.

AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

Model ASF1072A is not licensed to bear the AMCA seal.

*Berner reserves the right to alter specifications without prior notice.*