

**REFRIGERATOR MANUFACTURER**  
**Turbo air**  
 more durable, convenient, beautiful

1250 Victoria St  
 Carson, CA 90746  
 Tel. 310-900-1000  
 Fax. 310-900-1077  
[www.turboairinc.com](http://www.turboairinc.com)

Project :

Model # :

Item # :

Qty :

Available W/H :

Approval :

## Side Mount Undercounter Ref.

Undercounters  
 J Series

**Model : JUR-48**



### FEATURES / BENEFITS

#### ■ HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

#### ■ SIDE MOUNT COMPRESSOR UNIT

Through positioning the compressor to the side, the refrigerator can be serviced without being moved. By innovatively creating a **front breathing** feature, this model can provide high efficiency in narrow spaces.

#### ■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### ■ EXTERIOR & INTERIOR OF THE CABINET

The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

#### ■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

#### ■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

#### ■ ADJUSTABLE, HEAVY DUTY, PE (POLYETHYLENE) COATED WIRE SHELVES

#### ■ ERGONOMICALLY DESIGNED DOORS


Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

#### ■ REFRIGERATOR HOLDS 33°F ~ 39°F FOR THE BEST IN FOOD PRESERVATION



| Model         | Swing Door | CU./FT.   | #of Shelves | HP         | AMPS       | Crated Weight (lbs.) | L x D* x H† (inches)            |
|---------------|------------|-----------|-------------|------------|------------|----------------------|---------------------------------|
| <b>JUR-48</b> | <b>2</b>   | <b>11</b> | <b>2</b>    | <b>1/4</b> | <b>4.5</b> | <b>205</b>           | <b>47 1/4 x 27 1/2 x 28 3/4</b> |

## Model : JUR-48

| ELECTRICAL DATA          |  |
|--------------------------|--|
| Voltage                  | 115/60/1   |
| Plug Type                |  NEMA-5-15P |
| Full Load Amperes        | 4.5  |
| Compressor HP            | 1/4  |
| Cord Length ft.          | 9.2  |
| Refrigerant              | R-134A   |
|                          |  |
| DIMENSIONAL DATA         |  |
| Net Capacity cu. ft.     | 11   |
| Ext. Length Overall in.  | 47 1/4 (1200mm)  |
| Ext. Depth Overall in.*  | 27 1/2 (699mm)   |
| Ext. Height Overall in.† | 28 3/4 (730mm)   |
| # of Doors               | 2  |
| # of Shelves             | 2  |
| Gross Weight lbs.        | 205  |
| Net Weight lbs.          | 184  |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

\*Depth does not include 1" for rear spacers.

† Height does not include 5-7/8" for caster height.

- **WARRANTY :** 1 Year Parts and Labor Warranty  
Additional 4 Year Warranty on Compressor


- **SELF-CONTAINED SYSTEM**
- **4" DIAMETER CASTERS ARE STANDARD**
- **2.5" DIA. CASTERS AVAILABLE (OPTIONAL)**
- **LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)**

### ■ OPTIONAL ACCESSORIES :


- ☐ 2.5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional PE coated wire shelves
- ☐ Stainless steel double over-shelf
- ☐ Back splash guard

## PLAN VIEW


(unit : inch)



## PLAN VIEW



## FRONT VIEW



## SIDE VIEW

Ver.201203



- Turbo Air : 800-627-0032 ■ GK : 800-500-3519
- Warranty : 800-381-7770 ■ AC : 888-900-1002