

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:	
Model #:	
Item #:	Qty:
Available W/H :	
Approval :	

# Side Mount Undercounter Ref.

**Undercounters** J Series

**Model : JUR-60** 



## 🚅 FEATURES / BENEFITS 🖳

### ■ HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

#### Side Mount Compressor Unit

Through positioning the compressor to the side, the refrigerator can be serviced without being moved. By innovatively creating a front breathing feature, this model can provide high efficiency in narrow spaces.

#### ■ Efficient Refrigeration System

Turbo Air's solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### EXTERIOR & INTERIOR OF THE CABINET

The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined setting.

#### ■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-inplace using high density, CFC free polyurethane insulation.

### ■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

## ■ ADJUSTABLE, HEAVY DUTY, PE (POLYETHYLENE) COATED WIRE SHELVES

### ■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

## ■ REFRIGERATOR HOLDS 33°F ~ 39°F FOR THE BEST IN FOOD PRESERVATION











JUR-60	2	15	2	1/4	4.8	240	59 x 271/2 x 283/4
Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H <sup>†</sup> (inches)

(unit: inch)

# Side Mount Undercounter Ref.

## **Model: JUR-60**

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA-5-15P				
Full Load Amperes	4.8				
Compressor HP	1/4				
Cord Length ft.	9.2				
Refrigerant	R-134A				
DIMENSIONAL DATA					
Net Capacity cu. ft.	15				
Ext. Length Overall in.	59 (1499mm)				
Ext. Depth Overall in.*	27 <sub>1/2</sub> (699mm)				
Ext. Height Overall in.†	28 <sub>3/4</sub> (730mm)				
# of Doors	2				
# of Shelves	2				
Gross Weight lbs.	240				
Net Weight lbs.	205				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


# ■ WARRANTY: 1 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor


- SELF-CONTAINED SYSTEM
- 4" DIAMETER CASTERS ARE STANDARD
- 2.5" DIA. CASTERS AVAILABLE (OPTIONAL)
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)

#### ■ OPTIONAL ACCESSORIES:


- ☐ 2.5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional PE coated wire shelves
- ☐ Stainless steel double over-shelf
- Back splash guard

## **PLAN VIEW**





**FRONT VIEW** 



SIDE VIEW












Ver.201203



■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup>Depth does not include 1" for rear spacers.

<sup>†</sup> Height does not include 5-7/8" for caster height.