

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Undercounter Freezer

Undercounters M3 Series

Model: MUF-48



___FEATURES / BENEFITS =___

- STAINLESS STEEL CABINET CONSTRUCTION The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. It can add a touch of style to the most refined
- HOT GAS CONDENSATE SYSTEM

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ EFFICIENT REFRIGERATION SYSTEM

M3's solid door freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

■ High-Density Polyurethane Insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- ADJUSTABLE, HEAVY DUTY, PE (POLYETHYLENE) COATED WIRE SHELVES
- ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ Freezer Holds -5°F ~ -10°F for the Best IN FROZEN FOOD PRESERVATION











Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
MUF-48	2	12	2	1/2	8.3	246	481/4 x 30 x 30

(unit: inch)

Undercounter Freezer

Model: MUF-48

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	8.3				
Compressor HP	1/2				
Cord Length ft.	9				
Refrigerant	R-404A				
DIMENSIONAL DATA					
Net Capacity cu. ft.	12				
Ext. Length Overall in.	481/4 (1226mm)				
Ext. Depth Overall in.*	30 (762mm)				
Ext. Height Overall in.†	30 (762mm)				
# of Doors	2				
# of Shelves	2				
Gross Weight lbs.	246				
Net Weight lbs.	229				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 1 Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor

- SELF-CONTAINED SYSTEM
- 4" SWIVEL CASTERS
- 2.5" DIA. CASTERS AVAILABLE (OPTIONAL)
- LEGS AVAILABLE FOR ALL MODELS (OPTIONAL)
- STAINLESS STEEL BACK SPLASH AVAILABLE (OPTIONAL)


■ OPTIONAL ACCESSORIES:

- 2.5" Diameter casters
- ☐ 5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional stainless steel shelves
- ☐ Additional PE coated wire shelves
- □ Back splash guard
- ☐ Stainless steel double over-shelf

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver.201203







Turbo air













^{*}Depth does not include 1" for rear spacers.

[†] Height does not include 5-7/8" for caster height.