

Amana® Commercial

Project #: _____

Item #: _____



Model RMS10D shown

Low Volume

This category of microwave is ideal for...

Applications:

- Vending
- Break rooms
- Espresso bars
- Nurses stations



All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times. 866-426-2621.

Low Volume

Amana Commercial Microwave Model RMS10D

Power Output

- 1000 watts of power.
- Full power only for simple operation.

Certified Oven for Commercial Applications

- Tested to higher standards for a commercial rating - required by most commercial insurance policies and health inspectors.
- Interlock safety switch is tested to 4 times the standard of residential ovens.
- Constructed to withstand the foodservice environment, multiple users and variable ambient temperatures.
- Compared to a residential oven, this oven is more powerful for faster heating and better quality results.
- Engineered for a simple, "self-service" operation.

Easy to Use

- User friendly dial timer designed for self-serve applications.
- 6 minute digital timer lights up for "at-a-glance" monitoring.
- Timer automatically resets to zero if door is open during heating.
- See-through door and lighted interior for monitoring without opening the door.
- 0.9 cubic foot (.025m³) capacity accommodates a 12" (305mm) platter, prepackaged foods and single servings.

Easy to Maintain

- Stainless steel exterior wrap and painted interior for easy cleaning and a commercial look.
- Limited 3 year warranty.
- Backed by the ACP, Inc. 24/7 ComServ Support Center, 866-426-2621.
- UL and ETL Listed.




A/A File #:

Specification #:




Amana Commercial Microwave Model RMS10D | Low Volume



Installation clearance: 3" all sides

Specifications

Model	RMS10D	UPC Code 728028020786
Configuration	Countertop	
Control System	Dial	
Max. Cooking Time	6:00	
Power Levels	1	
Time Entry Option	Yes	
Microwave Distribution	Rotating stirrer, bottom	
Magnetron	1	
Stage Cooking	1 stage	
Interior Light	Yes	
Door Handle	Grab & Go	
Signal	End of cycle	
Exterior Dimensions	H 12 1/4" (311.15) W 20" (508)	D* 16 1/2" (419)
Cavity Dimensions	H 7 3/4" (196.85) W 13" (330.2)	D 13" (330.2)
Door Depth	29 1/2" (749.3), 90°+ door open	
Usable Cavity Space	0.9 cubic ft. (.025m ³)	
Exterior Finish	Stainless steel wrap	
Interior Finish	Painted	
Power Consumption	1150 W, 9.6 A	
Power Output**	1000 W** Microwave	
Power Source	120V, 60 Hz, 15 A single phase	
Plug Configuration / Cord	NEMA 5-15	5 ft. (1.5m) 
Frequency	2450 MHz	
Product Weight	32 lbs. (14.5 kg.)	
Ship weight (approx.)	39 lbs. (17.7 kg.)	
Shipping Carton Size	H 15" (381)	W 23" (584.19) D 18" (457.2)

Measurements in () are millimeters

* Includes handle

**IEC 705 Tested

Specifications

Commercial microwave shall have a user-friendly 6 minute dial timer with illuminated digits and end of cycle audible signal. Timer shall automatically reset to zero if the door is opened during heating. Oven shall have one power level - full power. Microwave output shall be 1000 watts distributed by one magnetron with a bottom feed rotating stirrer to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90°+ opening for easy access. An interior light shall facilitate monitoring without opening the door. The 0.9 cubic ft. (.025 m³) cavity shall accommodate a 12" (305 mm) platter. Oven shall have a stainless steel exterior wrap and white powder coat painted interior. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services, UL for safety and ETL for sanitation.



Warranty

Limited 3 year warranty:

Year 1 - parts, labor, and travel are covered.

Years 2 - 3 - magnetron tube (part only) is covered.

Service

All products are backed by the ACP, Inc. 24/7 ComServ Support Center.

